



BLAST CHILLERS

Features and Benefits

- **Safe food handling** An optimal way to rapidly decrease the temperature of food minimizing bacteria growth. Constructed to meet HACCP regulations.
- **High quality chill and versatility** Work with hard chill, soft chill, hard freeze and soft freeze. Obtain constancy with access of up to 100 programs.
- **Product organization** Implement a cook and chill process in your kitchen for a better management of inventory.
- **Efficiency** The chilling cycle will go from 194°F to 37°F in 90 minutes. The freeze cycle will go from 194°F to 0°F in 240 minutes.
- **Precision** Core temperature probe equipped.
- **Environmentally safe** High density polyurethane foam insulation which is **CFC & HCFC FREE**.
- **High quality construction** With internal and external finish of ANSI-304, 18/10 Stainless Steel with a scotch brite exterior finish.
- **Warranty** (1) year parts and labor, (3) years compressor.



■ OBF084 AF



■ OBF051 AF



■ OBF054 AF



Conforms to
UL Std. 471
& CAN/CSA
Std. C22.2 No. 120



Conforms to
NSF Std. 07



Made in Italy



Please consult our web site www.eurodib.com for additional information on other product lines.
US 1320 Route 9, Champlain NY, 12919 | **CAN** 120 rue de la Barre, Boucherville, Qc J4B 2X7
Tel.: **1 888 956 6866** | Fax: **1 877 956 6867** | www.eurodib.com

Blast Chillers

Technical

Models	Dimensions H x W x D (in)	Door opening width	Door opening height	Internal depth	Thickness	Capacity
OBF051 AF	33.5 x 31.1 x 27.5	26.3	15	18.7	2.4	5 - 21" x 13" sheet pans (not included)
OBF054 AF	33.5 x 33.5 x 29.9	28.7	15	18.7	2.4	5 - 26" x 18" sheet pans (not included)
OBF084 AF	52 x 33.5 x 33.5	28.7	24.8	20.1	2.4	8 - 26" x 18" sheet pans (not included)

CONT.

Models	Freezing cap. (lbs)	Refrigerant	Electric power supply (Hz)	Watts	HP	Amp	Noise level dB (A)	Net weight
OBF051 AF	26	R404A	208-240/1/60	1167	1.5	6.1	<70	254 lbs
OBF054 AF	26	R404A	208-240/1/60	1167	1.5	6.1	<70	254 lbs
OBF084 AF	35	R404A	208-240/1/60	1786	2.5	10.1	<70	331 lbs

mod—M—(*) Temp. evap. -25°C Temp. cond. *45° / Temp. evap. -10°C Temp. cond. *55°

