

KATTEX

OPERATION AND MAINTENANCE INSTRUCTIONS

ONION QUICK SLICER

PLEASE NOTE: Careful and close adherence with the below instructions will help enhance the operation and longevity of your KATTEX Onion Quick Slicer. Ensure to thoroughly clean the device prior and after each use, complying by the cleaning instructions below. Minimize the use of alkaline cleansers as they may cause pitting and dulling of the finish.

SAFETY REMINDER: The blades are VERY SHARP. Please exercise caution when handling and operating the machine and keep hands away from all cutting edges and blades.

PREPARATION

1. The lever can be locked in the up position to safely and conveniently clean the blade assembly and pusher assembly. Raise the lever so that the hole aligns with the holes in the link bars and insert the pin through all three parts.
2. Insert the pin through the unused hole in the handle while the machine is in use so that it will not be misplaced.
3. If the unit fails to properly operate during its first use, call Winco customer service at 1-888-946-2682, or email at cs@wincous.com.

TO OPERATE

1. Hold the lever in its up position and place the produce so that it is near the center of the blade pattern.
2. Remove hand / fingers from the cutting area, and with one smooth, quick motion, bring the lever down to cause the pusher assembly to force the produce through the blades. Lift and repeat as necessary.

CLEANING

1. To remove the pusher assembly, remove the pin, move the lever out of the way and lift the pusher assembly off of the guide rods.
2. To remove the blade assemblies, lock the pusher assembly in the up position, and remove the blade assemblies off of the pins, one at a time. Clean the blade assemblies and replace one at a time over the locating pins while the handle is still locked in the up position. Now remove the handle from the locked out position and continue use.

TO LUBRICATE

As needed, lubricate the rods with food grade mineral oil. Do not lubricate with cooking or vegetable oil. Lubricating the rods with any other oil may cause the machine to malfunction.